

Technical Specifications

VEER 3000 4WD

Standard Features	4WD
Engine	
Make Model HP / kW No. of Cylinders Bore/Stroke (mm) Cubic Capacity (cc) Rated RPM Air Cleaner Max Torque (Nm @ RPM)	MITSUBISHI MVS3L2 26 HP / 18.2 kw 3 78/92 1318 2500 ± 30 Dry Air Cleaner with Clogging Sensor 76.3@2000
Transmission	
Drive Clutch Gearbox Transmission Type	4WD Single Clutch 6F + 2R Sliding Mesh
РТО	
Independent PTO PTO (actuation)	540 / 540 E Mechanically actuated, Hand operated
Electrical	
Battery (V, Ah) Alternator (V, A) Trailer Socket DCV	12, 65 12, 65 Yes, Seven Pin (Round)
DCV	Yes
Steering	
Steering	Power Steering
Tyre	
Front Rear	6.00 - 12 8.3 - 20
Speed Forward	
Min Speed (Km/h) @ rpm Max Speed (Km/h) @ rpm	1.32@2500 14.73@2500
Brakes	
Brakes Type of Actuation Hand Brake	Oil Immersed Disc Brakes Mechanically actuated Yes, Hand Operated

	4WD
Hydraulics	
Automatic Draft control	No
3 Point Linkage	CAT1N
Auxiliary Hydraulic Circuit	1DA
Hydraulic Lifting Capacity	600
(kg) hitch point	
Others	
Trailer Hitch	Optional (Rotating Type)
Driver Seat	Horizontally adjustable
Fuel Indicator Gauge	Yes
Front Tow Hook	Yes
ROPS	Yes
Weight	
Front Weight	Front weight carrier (hanging weight optional)
Rear Weight	No
Capacity (L)	
Fuel Tank	25
Power Steering System	1.8
Engine Oil	4
Hydraulic+Transmission	17
Front Axle	2.5
Dimension & Weight	
Weight (kg)	1040
Wheel Base (mm)	1365
Total Length (mm)	2710
Total Width (mm)	1170
Height (mm)	2500
Ground Clearance (mm)	227
Front Track, (mm), min-max	940
Rear Track, (mm), min-max	870
Optional Features	
Industrial Tyre (Front, Rear)	23x8.50-12 & 33x15.5-16.5
Turf Tyre (Front, Rear)	23x8.50-12 & 33x15.5-16.5



Marketing Head Office

4th Floor, Pinnacle, Surajkund, NCR-121009 (INDIA) Ph.: +91-129-4550000, Fax: +91-129-4550022 E-mail: exports@ace-cranes.com

Action Construction Equipment Ltd. Registered Office & Works

Dudholla Link Road, Dudholla , Palwal - 121102 INDIA, (Haryana) Ph.: +91-1275-280111, Fax: +91-1275-280133 CIN: L74899HR1995PLC053860

Website: www.ace-cranes.com



